

**PERFORMANCE**

°F   %RH	<b>80   60</b>	<b>75   50</b>
Water Removal (P/Day)	135	90
Efficiency (P/kWh)	7.2	4.4
Energy Factor (L/kWh)	3.4	2.1

**ELECTRICAL**

°F   %RH	<b>80   60</b>
Supply Voltage	110-120
Current Draw	6.8A
MCA*	15A
MOP*	15A
Recommended Breaker Size	15A
Power	780W
Power Cord	14/3, SJTW, 115 VAC, 25'
Plug	NEMA 5-15P
CFM	300
BTU (Total)	8,850
BTU (Heat of Condensation)	6,200
BTU (Motor Load)	2,650

**SPECS**

Control Type	Onboard Digital
Refrigerant Type	R454b
Refrigerant Amount	1 lb 3 oz
Weight	85 lb
Air Filter MERV Rating	MERV-10
Dimensions	12" x 14" x 1"
Drain Port Connection	3/8" Push to Connect
Operating Temperature	55 F Min - 95 F Max

**DIMENSIONS**

**FEATURES**

- + **Patented M-CoRR™ Technology:** unique multi-coil design achieves highest efficiency available in its class
- + **12-Inch Recessed Wheels** for superior mobility, even on stairs
- + **Digital Onboard Control** for precise environmental control
- + **Internal Condensate Pump** capable of lifting condensate 20 feet along with a 33-foot drain hose for extended reach
- + **Convenient collapsible, stacking design** for space-saving storage
- + **25-Foot Power Cord** for convenient power access

Specifications are subject to change without notice. Drawings are not to scale. \*See manual for details on MCA/MOP.