

Introducing to the ILUMINAR Line-Up Dual Lamp 630W Ceramic Metal Halide Fixture. This is the ideal fixture for all your cultivating applications and is coming out on top, with the most effective dimmable controllable fixture and highest reflectivity on the reflector. The new ILUMINAR 630W Dual Lamp CMH offers extreme control of your yield with two opposing lights that enables the capacity to mix spectrums for an ideal full stage expansive range that will let all your plants achieve their highest potential. **Cleaner Light for Max Yields** Less Heat Reduced **Cooling Costs** 630 W Full Spectrum Uniform Light Distribution Low Frequency Ignition Failure Protection Square Wave Technology PHYSICAL SPECS CASE LENGTH 682mm / 27" CASE WIDTH 249mm / 9.8" **HEIGHT** 118mm / 4.6" WEIGHT 7kg / 15.43 lb

877.540.5588 x100 sales@iluminarlighting.com www.iluminarlighting.com



277V

## TECHNICAL INFO DUAL LAMP 630W CMH

INPUT VOLTS (+/- 10%)

**INPUT CURRENT** 

INPUT POWER

**VOLTAGE RANGE** 

THD

MAIN FREQUENCY

277V

2.60A

686W

249-290V

<15%

50/60 Hz



**Dimmable** 



**Smart Start Tech** 



**Energy Efficient** 

## ADDITIONAL TECHNICAL INFO

CONTROLLER

MIN POWER FACTOR

**CREST FACTOR** 

INPUT CONNECTION

INPUT FREQUENCY

DIMMING GEAR

**RELATIVE HUMIDITY** 

OPERATION TEMP.

RECOMMENDED LAMP

**ILUMINAR** Touch

.95

< 1.7

power cable 15' with 240 V NEMA 6-15 plug

48 - 63Hz

315 / 475 /630 / 675 / EXT

25-70% (Non-condensing)

-20 - 40°C / -4-104°F

315W x2







