

# K-22 pulsFOG®



## K-22 pulsFOG®

The Damm K-22 PulsFOG quickly applies chemical solutions as a fog. Able to treat up to 50,000 square feet with one tankful of solution in as little as 30 minutes, the K-22 will propel the fog up to 110 feet from the operator. The PulsFOG is great for the application of insecticides, fungicides, disinfectants, foliar fertilizers and for frost protection.

The K-22 is available in several versions: a standard model, an oil model and a BIO model. Standard is used for regular chemical solutions that are water-based and not heat-sensitive. The Oil version is for the application of flammable liquids. The BIO version utilizes a

second tank and nozzle system for plain water to water cool the engine exhaust for the application of heat-sensitive solutions.

The fast-fogging method allows for very quick application from a distance, reducing labor and chemical exposure.

PulsFOG units usually require the addition of a carrier solution added to the water and chemical mixture for best operation. Contact Damm for the proper solution for your needs.

### Specifications

Tank capacity Standard - 10 liter (50,000 sq ft)  
 BIO - one, 6 L & one, 5 L (30,000 sq ft)  
 Distance propelled VKII/NF - 110 ft  
 Force - 50 hp

Output - 10 liters/30 min  
 Fuel capacity - 2 liter  
 Power - 6 V (4: 1.5 V D batteries)  
 Weight empty - 18 lbs

\* PulsFOG® is a registered trademark of Dr. Stahl & Sohn GmbH & Co. KG

**DRAMM**  
 Integrated Plant Health

800.258.0848

information@damm.com  
 www.damm.com