QUEST HI-E DRY 195 | PN 4046400

PERFORMANCE

°F | %RH	80 | 60	75 | 50
Water Removal (P/Day)	195	145
Efficiency (P/kWh)	6.1	4.7
Energy Factor (L/kWh)	2.9	2.2

ELECTRICAL

°F | %RH	80 | 60
Supply Voltage	110-120 VAC
Current Draw	12A
MCA*	17A
MOP*	25A
Recommended Breaker Size	20A minimum
Power	1,385W
Power Cord	14 ga NEMA 5-20p
CFM	610
BTU (Total)	13,400
BTU (Heat of Condensation)	8,900
BTU (Motor Load)	4,500

SPECS

Control Type	Onboard
Refrigerant Type	R454b
Refrigerant Amount	1 lb 12 oz
Weight	130 lb
Air Filter MERV Rating	MERV-11
Dimensions	20" x 16" x 2"
Drain Port Connection	1/4" ID
Operating Temperature	56 F Min - 95 F Min



FEATURES

+ Added dehumidification where you need it with casters for easy transport
+ Extended reach with 10-foot power cord
+ Onboard digital dehumidistat
+ 30-foot drain hose with internal pump capable of lifting condensate 17 feet
+ Environmentally friendly refrigerant
+ Auto-restart after loss of power

Specifications are subject to change without notice. Drawings are not to scale. *See manual for details on MCA/MOP.