



# VORTEX PRO-LITE

## Carbon Filter

**Built in flange**


**Aluminum top & bottom to reduce weight and ease of installation**

**Large selection of sizes to meet all your air filtration needs**

**Antibacterial pre-filter included**

**51% perforated open area for maximum air flow**

**1.8" bed depth of pure virgin activated Australian light weight granular carbon**



## A Breath of Fresh Air

MODEL	Recommended Maximum CFM	Flange	Outside Diameter	Height	Weight	Carbon Bed Width	Recommended Fan	Pressure Drop at Max CFM
4 x 12	200	4"	7.5"	12in. 30.5cm	7.1lbs.	1.8" (46mm)	VTX400, VBC400	125pa/.0.5"wg
4 x 16	235	4"	7.5"	16in. 40.5cm	8.2 lbs.	1.8" (46mm)	VTX400, VBC400	125pa/.0.5"wg
6 x 16	400	6"	9.5"	16in. 40.5cm	9.9 lbs.	1.8" (46mm)	VTX600L, S-600, VBC600	125pa/.0.5"wg
6 x 24	550	6"	9.5"	24in. 70cm	14.9lbs.	1.8" (46mm)	VTX600, VTX600L, S-600, VBC600	125pa/.0.5"wg
8 x 24	750	8"	11.5"	24in. 70cm	19.6 lbs.	1.8" (46mm)	VTX800, VTX800L, S-800, VBC800	125pa/.0.5"wg
8 x 40	950	8"	11.5"	40in. 101cm	32.8 lbs.	1.8" (46mm)	VTX800, VTX800L, S-800, VBC800	125pa/.0.5"wg
10 x 40	1400	10"	13.4"	40in. 101cm	41.5 lbs.	1.8" (46mm)	VTX1000, S-1000, VBC1000	125pa/.0.5"wg
12 x 40	1700	12"	15.5"	40in. 101cm	58.5 lbs.	1.8" (46mm)	VTX1200, VTX1200L, VBC1200	125pa/.0.5"wg
14 x 40	2100	14"	17.5"	40in. 101cm	64.9 lbs.	1.8" (46mm)	VTX1200, VTX1200L, S-800, VBC1200	125pa/.0.5"wg
14 x 50	3500	14"	17.5"	50in. 127cm	72.1 lbs.	1.8" (46mm)	V-14XL	125pa/.0.5"wg

All Vortex PRO-lite products come with a PREfilter included

All Vortex PRO-lite have a Max Operating Temperature of 175°F

2480 Boul. des Entreprises Terrebonne, QC, Canada J6X 4J8  
Tel.: 450 477-1100 Fax: 514 313-5700 Toll Free: 1 800 489-1301  
Email: [info@atmosphere.com](mailto:info@atmosphere.com)

# WWW.ATMOSPHERE.COM