

Introducing to the ILUMINAR Line-Up Dual Lamp 630W Ceramic Metal Halide Fixture. This is the ideal fixture for all your cultivating applications and is coming out on top, with the most effective dimmable controllable fixture and highest reflectivity on the reflector. The new ILUMINAR 630W Dual Lamp CMH offers extreme control of your yield with two opposing lights that enables the capacity to mix spectrums for an ideal full stage expansive range that will let all your plants achieve their highest potential. **Cleaner Light for Max** Yields **Less Heat Reduced Cooling Costs** ◀ 630 W Full Spectrum Uniform Light Distribution Low Frequency ■ Ignition Failure Protection Square Wave Technology PHYSICAL SPECS CASE LENGTH 682mm / 27" CASE WIDTH 249mm / 9.8" HEIGHT 118mm / 4.6" 7kg / 15.43 lb **WEIGHT** 877.540.5588 x100 sales@iluminarlighting.com

www.iluminarlighting.com

ILUMINAR 120V/240V Commercial Grade Fixture

TECHNICAL INFO DUAL LAMP 630W CMH

INPUT VOLTS (+/- 10%)

INPUT CURRENT

INPUT POWER

VOLTAGE RANGE

THD

MAIN FREQUENCY

120V

240V

5.78A

2.86A

686W

108-264V

<15%

50/60 Hz



Dimmable



Smart Start Tech



Energy Efficient

ADDITIONAL TECHNICAL INFO

CONTROLLER

MIN POWER FACTOR

CREST FACTOR

INPUT CONNECTION

INPUT FREQUENCY

DIMMING GEAR

RELATIVE HUMIDITY

OPERATION TEMP.

RECOMMENDED LAMP

ILUMINAR Touch

.95

< 1.7

power cable 15' with 240 V NEMA 6-15 plug

48 - 63Hz

315 / 475 /630 / 675 / EXT

25-70% (Non-condensing)

-20 - 40°C / -4-104°F

315W x2







